

If taking the RIB out, the following points provide a checklist to ensure the boat is 'good to go'.

Ideally the list should be addressed the day before departure to ensure a good start and should be carried out on both the main and the spare (donkey) engine.

- 1. Remove the external cover, wheel clamp, hitch lock and engine cover
- 2. Ensure tyre and jack wheel braces are available, check tyre pressures and ensure tread is legal..

 Note: The spare wheel and road wheels have different sized wheel nuts.
- 3. Check the winch strap is connected to the front of the RIB
- 4. Ensure the safety chain/rope is connected to the front of the RIB
- 5. Ensure the rear ratchet straps connecting the boat to the trailer are tight and secure
- 6. Check the correct towing vehicle number plate is on the trailer
- 7. Connect the trailer jack plug to the vehicle and ensure indicator and brake lights are working
- 8. Check rear bungs in transom are secure
- 9. Check the brake safety cable
- 10. Ensure the transponder is in position
- 11. Dip fuel with graduated brush handle to ensure fuel tank full and pump primed
- 12. Check tubes are fully inflated ensure bellows are available
- 13. Turn batteries on and check all lights and switches on the boat and bulkhead
- 14. Check engine transom bolts. Remove engine support and lower engine to vertical position
- 15. Check 2-stroke premix oil level and ensure funnel is available
- 16. Connect muffs to engine and run water through ensuring the tail trail is flowing and output water is cool run for approximately 5 minutes.
- 17. Check the engine switch is operation and the kill cord fitted. Check location of spare kill cord.
- 18. Select forward and reverse gears, then return to neutral to ensure fully operational
- 19. Turn off engine and return it to the original position ensuring the engine is correctly propped
- 20. Replace bags over both props it is a legal requirement that they are covered
- 21. Erect the aerial, check the radio that it turns on.
- 22. Cross check the VHF radio with the handheld VHF
- 23. Attach the sonar/GPS, turn both on to ensure they start then turn off as it can cause damage to the transponder if left on whilst out of the water.
- 24. Turn the battery switch to Off, lower and secure the aerial



- 25. Check the contents and operation of the O2 (Oxygen) cylinder and mask
- 26. Ensure the following are in either in the boat boxes or on the boat:
 - AFrame Box of tools including spare spark plugs/split pins
 - AFrame Box of flares within test date
 - Fire extinguisher within test date
 - Aframe First Aid Kit with supplies within test date
 - 02 set
 - 2 x small oars
 - 1 handheld VHF radio
 - Compass
 - 1 A-flag on pole
 - Anchor box contain sufficient spare warp, chain and types of anchor. Other lines for mooring or tying off e.g. spring lines, jetties etc, tell-tails and marker buoys for shot line Fenders
 - 1 knife
 - Foot pump (bellows) for tubes
 - A plug-in search light
 - Throw line (in a bag)
 - Spare 2-stroke oil
 - Spare fuel for the donkey engine
- 27. The cox has completed a voyage plan
- 28. Dive logs are available
- 29. The crew have personal buoyancy devices, food, money, fresh water etc
- 30. Go diving, stay safe and have a great time

Name:	Date:
Notes / broken / missing:	